



DATA

SHEET BT-1015

1000 bar Hand Pump BT-1015

This hand pump can be used with all BOLTIGHT 1000 bar tooling and equipment. The pump has both high and low pressure pistons and is supplied complete with, a 110 mm damped (liquid filled) pressure gauge, pressure release valve, internal pressure safety relief valve, a 2.4 litre oil reservoir and a self sealing quick connect coupling (Type A - see DS26).

Hand pumps should only be used with one or two tensioning tools. When simultaneous operation of several tools is being considered BOLTIGHT recommends the use of an air driven pump.









Note

A hand pump with a 1 litre oil reservoir and a smaller 63 mm diameter pressure gauge is also available.

Ask for Part No BT-1014.

Specification:

Part No

Dimensions Weight Oil Reservoir Finish Pressure Gauge Maximum Pressure Oil Delivery Low Pressure Piston Oil Delivery High Pressure Piston

Handle Effort @ 1000 bar

BT-1015 620 mm long x 130 mm wide x 170 mm high 10.1 kgs 2.4 litre ISO 10 hydraulic oil Aluminium Silver 0 - 1500 bar (0-22,000 psi) 110 mm diameter 1500 bar but internal pressure relief set at 1000 bar 20 cc per stroke 1 cc per stroke 230 Newtons

Email: sales@boltight.com Web: www.boltight.com Copyright Boltight Ltd Aug 2011